

The compact, versatile platform AGV

Melkus C4060

Without the load carrier, the smart platform AVG measures only 40 x 60 x 21 cm and is with 29 kg a lightweight. With the self-guided Melkus C4060, smaller, internal transports in production and logistics can be handled safely and efficiently. The C4060 can be equipped with various load carriers.

Technical Data


Load capacity:	100 kg
Speed:	1.5 m/s
Navigation:	SLAM navigation
Dimensions:	40 cm x 60 cm x 21 cm (W x L x H)
Weight:	29 kg – without load carrier

 **SIGMA** *motion*

Melkus Mechatronic

The compact, versatile platform AGV

Melkus C4060



Flexible

- Compact construction and small turn radius allows use in the tightest space
- SLAM navigation
- Simple integration of customer-specific load carriers

Efficient

- High availability: up to 8-hr battery life, fast charging of the LiFePo4 high-performance power-pack
- Smooth material transport using clever drive technology
- Easy change of transport sequence



Intelligent

- Compact automation solution from SIGMATEK
- High personnel safety via 2 laser scanners
- WLAN communication with the guidance system
- Operation and diagnostics also with smart devices

Versatile

- SLC-transport
- Point-to-point transport tasks
- Flexible link between stationary transport routes
- Different load carriers for seamless material transfer

